

## SEARCH REQUEST FORM

Scientific and Technical Information Center

Requester's Full Name: Cephia Toomey Examiner #: 71652 Date: 8/28/01  
Art Unit: 1714 Phone Number 30 8-2509 Serial Number: 09/6/993  
Mail Box and Bldg/Room Location: CP3 4D11 Results Format Preferred (circle): PAPER DISK E-MAIL

If more than one search is submitted, please prioritize searches in order of need.

\*\*\*\*\*  
Please provide a detailed statement of the search topic, and describe as specifically as possible the subject matter to be searched. Include the elected species or structures, keywords, synonyms, acronyms, and registry numbers, and combine with the concept or utility of the invention. Define any terms that may have a special meaning. Give examples or relevant citations, authors, etc, if known. Please attach a copy of the cover sheet, pertinent claims, and abstract.

Title of Invention: Method and Composition for protecting Civil Infrastructure  
Inventors (please provide full names): Carbonell et al

Earliest Priority Filing Date: 10/10/97

\*For Sequence Searches Only\* Please include all pertinent information (parent, child, divisional, or issued patent numbers) along with the appropriate serial number.

A composition useful for protecting civil infrastructure said composition consisting essentially of between 80 and 99.9%  $CO_2$  and between about 0.1 and 20% of a fluoropolyether, said fluoropolyether having at least one anchoring group covalently joined thereto.

Said anchoring group is selected from amides, ester, Carboxylic acids, urethanes, ureas and mercaptans.  
Especially those underlined.

Thanks

## STAFF USE ONLY

	Type of Search	Vendors and cost where applicable
Searcher: <u>EL</u>	NA Sequence (#) <u>STN</u>	<u>\$131.13</u>
Searcher Phone #: _____	AA Sequence (#) _____	Dialog _____
Searcher Location: _____	Structure (#) <u>(1)</u>	Questel/Orbit _____
Date Searcher Picked Up: _____	Bibliographic <u>(2)</u>	WebLink _____
Date Completed: <u>(8-24-01)</u>	Litigation _____	Lexis/Nexis _____
Searcher Prep & Review Time: <u>5</u>	Fulltext _____	Sequence Systems _____
Clerical Prep Time: _____	Patent Family _____	WWW/Internet _____
Online Time: <u>60</u>	Other _____	Other (specify) _____



EIC 1700 / Lutrelle F. Parker Law Library



*Scientific and Technical Information Center*

## Search Results Feedback Form

The search results generated for your recent request are attached. If you have any questions or comments (compliments or complaints) about the scope or the results of the search, please contact the searcher whose name is circled below.

Kathleen Fuller

Eric Linnell ✓

Tim Saunders

All the searchers are located in the library in CP3/4 3D62

=> d 14 1-3 all

L4 ANSWER 1 OF 3 HCAPLUS COPYRIGHT 2001 ACS  
AN 1999:347680 HCAPLUS  
DN 131:116844  
TI Supercritical CO2 as a solvent for polymeric stone protective materials  
AU Henon, F. E.; Camaiti, M.; Burke, A. L. C.; Carbonell, R. G.; DeSimone, J. M.; Piacenti, F.  
CS Department of Chemical Engineering and Kenan Center for the Utilization of CO2 in Manufacturing, North Carolina State University, Raleigh, NC, 27695-7905, USA  
SO J. Supercrit. Fluids (1999), 15(2), 173-179  
CODEN: JSFLEH; ISSN: 0896-8446  
PB Elsevier Science B.V.  
DT Journal  
LA English  
CC 36-7 (Physical Properties of Synthetic High Polymers)  
AB The utilization of CO2 as a potential solvent for fluoropolymers used for the protection of civil infrastructures (buildings, bridges, monuments, etc.) is of major environmental as well as economic importance. The cloud points of six perfluoropolyethers at different wt. concns. in CO2 have been measured over a wide range of pressures. The results show that these fluorinated polymers are readily sol. in pure CO2 (no cosolvent or surfactant needed) at temps. close to 30.degree.C and pressures below 210 bars. The solubilities of the different polymeric products are strongly depend on the polymer hydrogen content and mol. wt.  
ST perfluoropolyether protective coating supercrit solvent; carbon dioxide supercrit solvent fluoropolymer; stone protective coating supercrit solvent  
IT Polyethers, uses  
(perfluoro; supercrit. carbon dioxide as solvent for perfluoropolyethers used as stone protection materials)  
IT Fluoropolymers, uses  
(polyether-; supercrit. carbon dioxide as solvent for perfluoropolyethers used as stone protection materials)  
IT Stone (construction material)  
(supercrit. carbon dioxide as solvent for perfluoropolyethers used as stone protection materials)  
IT Solvents  
(supercrit.; supercrit. carbon dioxide as solvent for perfluoropolyethers used as stone protection materials)  
IT Coating materials  
(weather-resistant; supercrit. carbon dioxide as solvent for perfluoropolyethers used as stone protection materials)  
IT 124-38-9, Carbon dioxide, uses  
(supercrit. carbon dioxide as solvent for perfluoropolyethers used as stone protection materials)  
RE.CNT 42

- RE.
- (1) Brady, J; Journal of Physical Chemistry 1985, V89, P1813 HCAPLUS
  - (2) Carbonell, R; Method and compositions for protecting civil infrastructure 1997
  - (3) Cece, A; Journal of Physical Chemistry 1996, V100, P7435 HCAPLUS
  - (4) DeSimone, J; Science 1992, V257, P945 HCAPLUS
  - (5) Diep, P; Journal of Physical Chemistry 1998, V102, P2231 HCAPLUS
  - (6) Enick, R; Journal of Supercritical Fluids 1998, V13, P127 HCAPLUS
  - (7) Frediani, P; Studies in Conservation 1982, V27, P31 HCAPLUS
  - (8) Gianotti, G; La Chimica e l'Industria 1991, V73, P463 HCAPLUS
  - (9) Helmick, L; Lubrication Engineering 1994, V50(6), P449 HCAPLUS
  - (10) Hoefling, T; Journal of Supercritical Fluids 1992, V5, P237 HCAPLUS
  - (11) Hoy, K; Proceedings of the Polymer Preprints - Division of Polymer Chemistry 1990, V31(1), P679 HCAPLUS
  - (12) Johns, K; Journal of Physics D: Applied Physics 1992, V25(1A), PA141 HCAPLUS
  - (13) Kasai, P; Applied Surface Science 1991, V51(3/4), P201
  - (14) Kasai, P; Applied Surface Science 1991, V52(1/2), P91
  - (15) Kasai, P; Macromolecules 1992, V25, P6791 HCAPLUS
  - (16) Lele, A; AIChE Journal 1992, V38(5), P742 HCAPLUS
  - (17) Manganelli, C; Science and Technology for Cultural Heritage 1992, V1, P201
  - (18) Matson, D; Industrial Engineering Chemistry Research 1987, V26, P2298 HCAPLUS
  - (19) Matson, D; Materials Letters 1986, V4(10), P429 HCAPLUS
  - (20) Matteoli, U; Proceedings of the 6th International Congress on Deterioration and Conservation of Stone 1988, P509
  - (21) Mawson, S; Macromolecules 1995, V28, P3182 HCAPLUS
  - (22) McHugh, M; Supercritical Fluid Extraction: Principles and Practice 1994, V2nd
  - (23) Meilchen, M; Macromolecules 1991, V24, P4874 HCAPLUS
  - (24) Mohamed, S; AIChE Journal 1989, V35(29), P325
  - (25) Ohsaka, Y; Petrotech 1985, V8(9), P840 HCAPLUS
  - (26) Pasetti, A; L'Edilizia 1990, V5(4), P329
  - (27) Pasetti, A; L'Edilizia 1990, V6(4), P413
  - (28) Petersen, R; Journal of the American Chemical Society 1986, V108(8), P2100 HCAPLUS
  - (29) Piacenti, F; US 4499146 HCAPLUS
  - (30) Piacenti, F; Journal of Fluorine Chemistry 1994, V68, P227 HCAPLUS
  - (31) Piacenti, F; Proceedings of the 7th International Congress on Deterioration and Conservation of Stone 1992, V3, P1223
  - (32) Piacenti, F; Proceedings of the International RILEM/UNESCO Congress on Conservation of Stones and Other Materials 1993, V2, P733
  - (33) Piacenti, F; The Science of the Total Environment 1994, V143, P113 HCAPLUS
  - (34) Pianca, M; Chemistry Today 1995, V1(2), P29
  - (35) Reid, C; The properties of gases and liquids 1987, V4th, P587
  - (36) Rindfleisch, F; Journal of Physical Chemistry 1996, V100, P15581 HCAPLUS
  - (37) Sianesi, D; Wear 1971, V18, P85 HCAPLUS
  - (38) Solomon, S; Nature 1986, V321, P755 HCAPLUS
  - (39) Strepparola, E; US 4746550 HCAPLUS
  - (40) Tom, J; Journal of Aerosol Science 1991, V22(5), P555 HCAPLUS
  - (41) Tuminello, W; Macromolecules 1995, V28, P1506 HCAPLUS
  - (42) Yee, G; Journal of Physical Chemistry 1992, V96, P6172 HCAPLUS

DN. 130:298067  
 TI Coating compositions and their application for protecting civil  
 engineering infrastructure from pollution effects  
 IN Carbonell, Ruben G.; Desimone, Joseph M.;  
 Henon, Florence E.  
 PA North Carolina State University, USA; The University of North  
 Carolina At Chapel Hill  
 SO PCT Int. Appl., 20 pp.  
 CODEN: PIXXD2  
 DT Patent  
 LA English  
 IC ICM B05D001-02  
 ICS B05D003-02  
 CC 42-10 (Coatings, Inks, and Related Products)  
 Section cross-reference(s): 58

FAN.CNT 1

	PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
PI	WO 9919080	A1	19990422	WO 1998-US21175	19981008
	W: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GM, HR, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, VZ, VN, YU, ZW, AM, AZ, BY, KG, KZ, MD, RU, TJ, TM				
	RW: GH, GM, KE, LS, MW, SD, SZ, UG, ZW, AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG				
	US 6127000	A	20001003	US 1997-948733	19971010
	AU 9910710	A1	19990503	AU 1999-10710	19981008
	EP 1051264	A1	20001115	EP 1998-953303	19981008
	R: AT, BE, CH, DE, DK, ES, FR, GB, GR, IT, LI, LU, NL, SE, MC, PT, IE, FI				
	JP 11256093	A2	19990921	JP 1998-288957	19981012
PRAI	US 1997-948733	A	19971010		
	WO 1998-US21175	W	19981008		
AB	The title sprayable coating compn. comprises CO2 carrier and a fluorocarbon such as a fluoropolyether (preferably a perfluoropolyether) or a fluorocarbon elastomer, optionally having .gtoreq.1 anchoring group such as an amide.				
ST	fluoropolyether carbon dioxide coating building material; fluoro rubber carbon dioxide coating building material				
IT	Bricks Cement (construction material) Ceramics Concrete (coating compns. for protecting civil engineering infrastructure from pollution effects)				
IT	Stone (construction material) (coating compns. for protecting civil engineering infrastructure from pollution effects)				
IT	Fluoro rubber (coating compns. for protecting civil engineering infrastructure from pollution effects)				
IT	Coatings (fluoropolymer in carbon dioxide; coating compns. for protecting civil engineering infrastructure from pollution effects)				
IT	Spray coating				

(of fluoropolymer in supercrit. carbon dioxide phase material)  
IT Polyethers, uses  
(perfluoro; coating compns. for protecting civil engineering infrastructure from pollution effects)  
IT Fluoropolymers, uses  
(polyether-; coating compns. for protecting civil engineering infrastructure from pollution effects)  
IT 124-38-9, Carbon dioxide, uses  
((supercrit.) solvent, fluoropolymer soly. in; coating compns. for protecting civil engineering infrastructure from pollution effects)

RE.CNT 2

RE

- (1) Desimone; US 5496901 A 1996 HCAPLUS  
(2) Piacenti; US 4745009 A 1988 HCAPLUS

L4 ANSWER 3 OF 3 HCAPLUS COPYRIGHT 2001 ACS

AN 1999:146243 HCAPLUS

TI Coatings from liquid and supercritical carbon dioxide

AU **Carbonell, Ruben G.; Henon, Florence E.**; Hoggan,  
Erik N.; Novick, Brian J.; **DeSimone, Joseph M.**; Kendall,  
Jonathan L.; Bunyard, William C.

CS Department of Chemical Engineering, North Carolina State University,  
Raleigh, NC, 27695-7905, USA

SO Book of Abstracts, 217th ACS National Meeting, Anaheim, Calif.,  
March 21-25 (1999), POLY-207 Publisher: American Chemical Society,  
Washington, D. C.  
CODEN: 67GHA6

DT Conference; Meeting Abstract

LA English

AB The discovery of surfactants and polymers that are sol. in carbon dioxide has greatly enhanced the possibilities for developing new coating processes using both liq. and supercrit. carbon dioxide as the carrier solvent. This paper summarizes recent results on coatings of fluoropolymers from supercrit. carbon dioxide, with particular application to the protection of stone materials and marine anti-fouling agents. Preliminary results are also presented on the development of new photoresists that are coated from liq. carbon dioxide by a spin-coating process. Finally, the potential for dip coating applications of sol. and dispersed polymers from liq. carbon dioxide will be discussed.

=> file reg

FILE 'REGISTRY' ENTERED AT 18:58:55 ON 28 AUG 2001  
USE IS SUBJECT TO THE TERMS OF YOUR STN CUSTOMER AGREEMENT.  
PLEASE SEE "HELP USAGETERMS" FOR DETAILS.  
COPYRIGHT (C) 2001 American Chemical Society (ACS)

=> display history full l1-

FILE 'HCAPLUS' ENTERED AT 18:15:12 ON 28 AUG 2001

L1 750 SEA CARBONELL ?/AU  
L2 721 SEA DESIMONE ?/AU  
L3 139 SEA HENON ?/AU  
L4 3 SEA L1 AND L2 AND L3  
L5 4447 SEA (FLUOROPOLYM? OR PERFLUOROPOLYM? OR FLUORINAT? OR  
PERFLUORINAT? OR FLUORO? OR PERFLUORO?) (2A) POLYETHER? OR  
FLUOROPOLYETHER# OR PERFLUOROPOLYETHER#

FILE 'REGISTRY' ENTERED AT 18:21:27 ON 28 AUG 2001

L6 E CARBON DIOXIDE/CN  
1 SEA "CARBON DIOXIDE"/CN

FILE 'HCAPLUS' ENTERED AT 18:26:27 ON 28 AUG 2001

L7 357383 SEA L6 OR CARBON#(2A)DIOXIDE# OR CO2  
L8 70175 SEA SCF OR S(W)C(W)F OR SUPERCRIT? OR SUPER?(2A)CRIT?  
L9 486129 SEA (BUILDING# OR CONSTRUCTION?) (2A) MATERIAL# OR BRICK?  
OR CEMENT? OR CONCRETE? OR CERAMIC? OR STONE# OR  
CINDERBLOCK? OR CINDER?(2A) BLOCK? OR MASONR? OR PORTLAND?  
OR GROUT? OR TERRAZZO?  
E COATING MATERIALS/CV  
L10 187386 SEA "COATING MATERIALS"/CV  
E COATING PROCESS/CV  
L11 86052 SEA "COATING PROCESS"/CV  
E COATING MATERIALS/CV  
L12 53424 SEA (ANCHOR? OR END? OR TERMINA?) (2A) GROUP? OR ENDCAP?  
OR ENDGROUP? OR ENDBLOCK? OR END?(2A) (CAP OR CAPS OR  
CAPPED OR CAPPING# OR BLOCK? OR GROUP?)  
L13 199 SEA L5 AND L7  
L14 48 SEA L13 AND L8  
L15 6 SEA L14 AND (L10 OR L11 OR L12)  
L16 3 SEA L14 AND L9  
L17 7 SEA L13 AND L9  
E COATING MATERIALS/CV  
L18 187386 SEA "COATING MATERIALS"/CV  
L19 2 SEA L14 AND (L10 OR L11 OR L18)  
L20 4 SEA L14 AND L12  
L21 375 SEA L5 AND L12  
L22 9 SEA L21 AND L7  
L23 0 SEA L22 AND (L10 OR L11 OR L18)

L24 4 SEA L22 AND L8

FILE 'REGISTRY' ENTERED AT 18:38:12 ON 28 AUG 2001

E FLUOROPOLYMER/PCT  
L25 8281 SEA FLUOROPOLYMER/PCT  
E POLYETHER/PCT  
L26 207716 SEA POLYETHER/PCT  
L27 728 SEA L26 AND L25  
L28 15185 SEA L26 AND F/ELS

FILE 'HCAPLUS' ENTERED AT 18:42:39 ON 28 AUG 2001

L29 383 SEA L27  
L30 8517 SEA L28  
L31 290 SEA (L29 OR L30) AND L7  
L32 14 SEA L31 AND L12  
L33 0 SEA L32 AND (L10 OR L11 OR L18)  
L34 0 SEA L32 AND L9  
L35 6 SEA L32 AND L8  
L36 431 SEA ANCHOR? (3A) (AMIDE# OR AMIDO# OR ESTER# OR CARBOXY?  
OR COOH OR CO2H OR URETHAN## OR UREA# OR THIOL# OR  
MERCAPT?)  
L37 0 SEA L31 AND L36  
L38 0 SEA L13 AND L36  
L39 5542 SEA L12 (3A) (AMIDE# OR AMIDO# OR ESTER# OR CARBOXY? OR  
COOH OR CO2H OR URETHAN## OR UREA# OR THIOL# OR MERCAPT?)  
L40 5 SEA L31 AND L39  
L41 3 SEA L13 AND L39  
L42 17 SEA L16 OR L17 OR L19 OR L20 OR L24 OR L35 OR L40 OR L41  
L43 4 SEA L22 NOT L42  
L44 5 SEA L32 NOT (L42 OR L43)

=> file hcaplus

FILE 'HCAPLUS' ENTERED AT 18:59:15 ON 28 AUG 2001  
USE IS SUBJECT TO THE TERMS OF YOUR STN CUSTOMER AGREEMENT.  
PLEASE SEE "HELP USAGETERMS" FOR DETAILS.  
COPYRIGHT (C) 2001 AMERICAN CHEMICAL SOCIETY (ACS)

=> d l42 1-17 ibib abs hitstr hitind

L42 ANSWER 1 OF 17 HCAPLUS COPYRIGHT 2001 ACS  
ACCESSION NUMBER: 2000:772728 HCAPLUS  
DOCUMENT NUMBER: 133:336899  
TITLE: Stabilized **carbon dioxide**  
fluid composition and use in cleaning and  
extraction applications  
INVENTOR(S): Senger, Elsbernd Cheryl L.  
PATENT ASSIGNEE(S): 3M Innovative Properties Company, USA  
SOURCE: PCT Int. Appl., 31 pp.



DOCUMENT TYPE: Patent  
 LANGUAGE: English  
 FAMILY ACC. NUM. COUNT: 2  
 PATENT INFORMATION:

CODEN: PIXXD2

PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
WO 2000065018	A1	20001102	WO 1999-US12509	19990604
W:	AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZA, ZW, AM, AZ, BY, KG, KZ, MD, RU, TJ, TM			
RW:	GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW, AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG			
US 6235701	B1	20010522	US 1999-299402	19990426
AU 9945466	A1	20001110	AU 1999-45466	19990604
PRIORITY APPLN. INFO.:			US 1999-299402	A 19990426
			CA 1998-2255413	A 19981211
			WO 1999-US12509	W 19990604


OTHER SOURCE(S): MARPAT 133:336899

AB A stable fluid comprises compressed fluid **CO2**, an inert gas, and a fluorochem. stabilizer. The fluid compn. is useful in cleaning of metals, glass, **ceramics**, natural and synthetic polymers, and fabrics and in the extn. of desirable substances, such as the extn. of essential oils from plants. An example dry cleaning fluid contained 0.17 g C4F9OCH2CH3 stabilizer, 5 mL **CO2**, and N (g).

IT 124-38-9, **Carbon dioxide**, uses  
 (compressed or **supercrit.**; stabilized **carbon dioxide** fluid compn. contg. inert gas and fluorochem. stabilizer)

RN 124-38-9 HCAPLUS

CN Carbon dioxide (8CI, 9CI) (CA INDEX NAME)



IC ICM C11D007-28

ICS C11D007-30; C11D007-50; C11D011-00

CC 46-5 (Surface Active Agents and Detergents)

ST **carbon dioxide** compressed fluid cleaning agent;  
 extn agent **carbon dioxide** stabilized fluid; dry  
 cleaning agent **carbon dioxide** stabilized fluid

IT Ethers, uses

(fluoroalkyl, stabilizer; stabilized **carbon dioxide** fluid compn. contg. inert gas and fluorochem. stabilizer)

- IT **Polyethers**, uses  
(**perfluoro**, stabilizer; stabilized **carbon dioxide** fluid compn. contg. inert gas and fluorochem. stabilizer)
- IT **Fluoropolymers**, uses  
(**polyether**-, stabilizer; stabilized **carbon dioxide** fluid compn. contg. inert gas and fluorochem. stabilizer)
- IT Dry cleaning solvents  
Wool  
(stabilized **carbon dioxide** fluid compn. contg. inert gas and fluorochem. stabilizer for cleaning)
- IT Extractants  
(stabilized **carbon dioxide** fluid compn. contg. inert gas and fluorochem. stabilizer for coffee)
- IT Coffee (Coffea)  
(stabilized **carbon dioxide** fluid compn. contg. inert gas and fluorochem. stabilizer for coffee extn.)
- IT Perfluorocarbons  
(stabilizer; stabilized **carbon dioxide** fluid compn. contg. inert gas and fluorochem. stabilizer)
- IT **124-38-9, Carbon dioxide**, uses  
(compressed or **supercrit.**; stabilized **carbon dioxide** fluid compn. contg. inert gas and fluorochem. stabilizer)
- IT 7727-37-9, Nitrogen, uses  
(stabilized **carbon dioxide** fluid compn. contg. inert gas and fluorochem. stabilizer)
- IT 311-89-7, FC-43 375-03-1 163702-05-4 163702-07-6  
(stabilizer; stabilized **carbon dioxide** fluid compn. contg. inert gas and fluorochem. stabilizer)

## REFERENCE COUNT:

8

## REFERENCE(S):

- (2) Archimex; FR 2771408 A 1999 HCAPLUS
- (3) Create Kk; JP 08041494 A 1996 HCAPLUS
- (4) E I Du Pont de Nemours And Company; WO 9728229 A 1997 HCAPLUS
- (5) Flynn, R; US 5962390 A 1999 HCAPLUS
- (6) Haky Hakuyosha Kk; JP 10018176 A 1998 HCAPLUS

ALL CITATIONS AVAILABLE IN THE RE FORMAT

L42 ANSWER 2 OF 17 HCAPLUS COPYRIGHT 2001 ACS

ACCESSION NUMBER: 2000:375551 HCAPLUS

DOCUMENT NUMBER: 133:120745

TITLE: Synthesis of Block Copolymers Containing a Main Chain Polymeric NLO Segment

AUTHOR(S): Pan, Jing; Chen, Mingfei; Warner, William; He, Mingqian; Dalton, Larry; Hogen-Esch, Thieo E.

CORPORATE SOURCE: Loker Hydrocarbon Research Institute and Department of Chemistry and University of Southern California, Los Angeles, CA, 90089-1661, USA

SOURCE: Macromolecules (2000), 33(13), 4673-4681

CODEN: MAMOBX; ISSN: 0024-9297

PUBLISHER: American Chemical Society

DOCUMENT TYPE: Journal

LANGUAGE: English

AB A poly-4-vinylpyridine-b-PNLO (nonlinear optical material)-b-polystyrene-b-poly(4-vinylphenol) tetrablock copolymer (P4VP-b-PNLO-b-PS-b-PVPh) was prepd., which contains an NLO polymeric segment prepd. by step polymn. The tetrablock copolymer is designed to form an asym. lamellar structure by self-assembly prompted by the interactions between the donor and acceptor blocks which are expected to help to align the dipole moments of PNLO block into one direction. The synthesis was carried out by reaction of a P4VP-b-PNLO-Ph-NH<sub>2</sub> block copolymer contg. an aniline end group with a poly(4-tert-butyl-dimethylsiloxy)styrene-b-PS-CO<sub>2</sub>H (PBDMSS-b-PS-COOH) diblock copolymer contg. a tert-butyl-dimethylsilyl-protected polyvinylphenol endowed with a **carboxylic end group** in the presence of diphenylphosphoryl azide (DPPA) in N,N-dimethylacetamide. After formation of the P4VP-b-PNLO-PhNH-CO-PS-b-PBDMSS tetrablock copolymer, the PVPh block was obtained by deprotection of tert-butyl-dimethylsilyl group of the PBDMSS block with tetrabutylammonium fluoride in THF. The PBDMSS-b-PS-COOH precursor was synthesized by initiation of 4-(tert-butyl-dimethylsilyl)oxystyrene by tert-butyllithium in THF at -78.degree. followed by addn. of styrene and end functionalized with dried **carbon dioxide** gas. The end-functionalized P4VP-b-PNLO-Ph-NH<sub>2</sub> block copolymer was synthesized by step polymn. of 4-(4-(4-fluorophenylsulfonyl)phenyl)sulfonyl-4'-N-ethyl-N-2-(4-hydroxyphenolic)ethyl-azobenzene and coupling to P4VP-Ph-OH that was end-functionalized with a phenolic end group followed by end capping with 4-(4-(4-fluorophenylsulfonyl)phenyl)sulfonyl-4'-N-ethyl-N-2-(4-aminophenolic)ethylazobenzene. The end-functionalized P4VP-Ph-OH was synthesized by the 1,1-diphenyl-3,3-dimethylbutyllithium-initiated polymn. of 4-vinylpyridine in THF at -78.degree. followed by addn. of 4-(tert-butyl-dimethylsiloxy)bromomethylbenzene.

IT 285555-45-5DP, desilylated

(step polymn. rout to tetrablock copolymers contg. main chain fluorophenylsulfonyl ethylazobenzene NLO segment and styrene-vinylpyridine-dimethylsiloxystyrene blocks)

RN 285555-45-5 HCAPLUS


CN Phenol, 4-[2-[ethyl[4-[[4-[[4-[(4-fluorophenyl)sulfonyl]phenyl]sulfonyl]phenyl]azo]phenyl]amino]ethoxy]-, polymer with (1,1-dimethylethyl)(4-ethenylphenoxy)dimethylsilane, ethenylbenzene and 4-ethenylpyridine, block (9CI) (CA INDEX NAME)

CM 1


CRN 224633-60-7

CMF C34 H30 F N3 O6 S2

PAGE 1-A




PAGE 1-B




CM 2

CRN 84494-81-5  
CMF C14 H22 O Si




CM 3

CRN 100-43-6  
CMF C7 H7 N



CM 4

CRN 100-42-5  
CMF C8 H8

IT 285555-45-5P

(tetrablock; step polymn. rout to tetrablock copolymers contg.  
main chain fluorophenylsulfonyl ethylazobenzene NLO segment and  
styrene-vinylpyridine-dimethylsiloxystyrene blocks)


RN 285555-45-5 HCAPLUS

CN Phenol, 4-[2-[ethyl[4-[[4-[[4-[(4-fluorophenyl)sulfonyl]phenyl]sulfonyl]phenyl]azophenyl]amino]ethoxy]-, polymer with  
(1,1-dimethylethyl)(4-ethenylphenoxy)dimethylsilane, ethenylbenzene  
and 4-ethenylpyridine, block (9CI) (CA INDEX NAME)


CM 1

CRN 224633-60-7  
CMF C34 H30 F N3 O6 S2

PAGE 1-A




PAGE 1-B



CM 2

CRN 84494-81-5


CMF C14 H22 O Si



CM 3

CRN 100-43-6


CMF C7 H7 N



CM 4

CRN 100-42-5

CMF C8 H8



CC 35-4 (Chemistry of Synthetic High Polymers)

Section cross-reference(s): 36, 73

IT 285555-45-5DP, desilylated

(step polymn. rout to tetrablock copolymers contg. main chain  
fluorophenylsulfonyl ethylazobenzene NLO segment and  
styrene-vinylpyridine-dimethylsiloxystyrene blocks)

IT 285555-45-5P

(tetrablock; step polymn. rout to tetrablock copolymers contg.  
main chain fluorophenylsulfonyl ethylazobenzene NLO segment and  
styrene-vinylpyridine-dimethylsiloxystyrene blocks)

REFERENCE COUNT:

51

REFERENCE(S):

- (1) Bates, F; Science 1991, V251, P898 HCAPLUS
- (2) Breiner, U; Macromol Chem Phys 1997, V198, P1051 HCAPLUS

- (3) Brinkmann, S; Macromolecules 1998, V31, P6566 HCAPLUS  
 (5) Chen, M; Polym Prepr 1999, V40(1), P158 HCAPLUS  
 (6) Chen, Z; Science 1997, V277, P1248 HCAPLUS  
 ALL CITATIONS AVAILABLE IN THE RE FORMAT

L42 ANSWER 3 OF 17 HCAPLUS COPYRIGHT 2001 ACS  
 ACCESSION NUMBER: 1999:819421 HCAPLUS  
 DOCUMENT NUMBER: 132:64669  
 TITLE: Addition dispersion polymerization in fluid reaction medium using removable stabilizers  
 INVENTOR(S): Irvine, Derek John; Christian, Paul; Howdle, Steven Melvyn  
 PATENT ASSIGNEE(S): Imperial Chemical Industries Plc, UK  
 SOURCE: PCT Int. Appl., 13 pp.  
 CODEN: PIXXD2  
 DOCUMENT TYPE: Patent  
 LANGUAGE: English  
 FAMILY ACC. NUM. COUNT: 1  
 PATENT INFORMATION:

PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
WO 9967297	A1	19991229	WO 1999-GB1830	19990609
W: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW, AM, AZ, BY, KG, KZ, MD, RU, TJ, TM				
RW: GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW, AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG				
AU 9942804	A1	20000110	AU 1999-42804	19990609
BR 9911485	A	20010320	BR 1999-11485	19990609
EP 1095065	A1	20010502	EP 1999-957170	19990609
R: AT, BE, CH, DE, DK, ES, FR, GB, GR, IT, LI, LU, NL, SE, MC, PT, IE, FI				

PRIORITY APPLN. INFO.: GB 1998-13573 A 19980624  
 WO 1999-GB1830 W 19990609



AB A title method comprises polymg. a homogeneous reaction mixt. including (a) at least one addn. polymerizable monomer, (b) a fluid reaction medium, preferably, **supercrit. carbon dioxide**, (c) a stabilizer, which is a material having a chain sol. in the **supercrit.** fluid and a functional **end-group** which is not polymerizable by a free-radical mechanism, and, optionally, (d) a chain transfer agent such as Bu mercaptan. At least one addn. polymerizable monomer is an ester of acrylic or methacrylic acids or substituted analogs thereof. A stabilizer comprises a functionalized fluoropolymer, siloxane, polyphosphazene or polyethylene oxide, preferably, an

acid-terminated **perfluoropolyether**, allows good control of the morfol. of the particles produced, and can be removed by venting along with the fluid medium. Thus, 10 g Me methacrylate, 1 wt.% Fomblin DA 601 (phosphate-terminated **perfluoropolyether**) and 1 wt.% azobis(isobutyronitrile) was polymd. in an autoclave for 4 h at 70.degree. and 200 bar CO<sub>2</sub>, giving a fine white polymer powder having av. particle size .apprx.2.7 .mu.m, polydispersity .apprx.2.7, and Mn 50 kD.

IT 51798-33-5, Krytox 157FSH 90317-74-1, Krytox 157FSL 106441-58-1, Krytox 157FSM  
(stabilizer; addn. dispersion polymn. in fluid reaction medium using removable stabilizers)

RN 51798-33-5 HCAPLUS


CN Poly[oxy[trifluoro(trifluoromethyl)-1,2-ethanediyl]],  
.alpha.-(1-carboxy-1,2,2,2-tetrafluoroethyl)-.omega.-  
[tetrafluoro(trifluoromethyl)ethoxy]- (9CI) (CA INDEX NAME)



4 ( D1-F )

RN 90317-74-1 HCAPLUS


CN Poly[oxy[trifluoro(trifluoromethyl)-1,2-ethanediyl]],  
.alpha.-(1-carboxy-1,2,2,2-tetrafluoroethyl)-.omega.-  
(heptafluoropropoxy)- (9CI) (CA INDEX NAME)




RN 106441-58-1 HCAPLUS



CN Poly[oxy[trifluoro(trifluoromethyl)-1,2-ethanediyl]],  
 .alpha.-(carboxydifluoromethyl)-.omega.-(pentafluoroethoxy)- (9CI)  
 (CA INDEX NAME)



IT 124-38-9, Carbon dioxide, uses  
 (supercrit.; addn. dispersion polymn. in fluid reaction  
 medium using removable stabilizers)  
 RN 124-38-9 HCAPLUS  
 CN Carbon dioxide (8CI, 9CI) (CA INDEX NAME)



IC ICM C08F002-04  
 CC 35-4 (Chemistry of Synthetic High Polymers)  
 ST dispersion polymn acrylic monomer **supercrit** fluid;  
**carbon dioxide supercrit** fluid addn  
 polymn; acid terminated **perfluoropolyether** stabilizer addn  
 polymn; butyl mercaptan chain transfer addn polymn  
 IT Fluoropolymers, uses  
 Polyoxyalkylenes, uses  
 Polyphosphazenes  
 Polysiloxanes, uses  
 (functional **group-terminated**; addn.  
 dispersion polymn. in fluid reaction medium using removable  
 stabilizers)  
 IT **Polyethers**, uses  
 (**perfluoro**, carboxylic acid-terminated; addn.  
 dispersion polymn. in fluid reaction medium using removable  
 stabilizers)  
 IT **Fluoropolymers**, uses  
 (**polyether-**, carboxylic acid-terminated; addn.  
 dispersion polymn. in fluid reaction medium using removable  
 stabilizers)  
 IT **Fluoropolymers**, uses  
 (**polyether-**, functionalized stabilizers; addn.  
 dispersion polymn. in fluid reaction medium using removable  
 stabilizers)  
 IT **Supercritical** fluids  
 (reaction medium; addn. dispersion polymn. in fluid reaction  
 medium using removable stabilizers)  
 IT 25322-68-3D, Polyethylene oxide, functional **group-**  
**terminated**  
 (addn. dispersion polymn. in fluid reaction medium using  
 removable stabilizers)

IT 51798-33-5, Krytox 157FSH 90317-74-1, Krytox  
157FSL 106441-58-1, Krytox 157FSM 176521-26-9,  
Fluorolink E 196623-59-3, Fluorolink C 253179-50-9, Galden MF  
300 253179-53-2, Fomblin DA 601  
(stabilizer; addn. dispersion polymn. in fluid reaction medium  
using removable stabilizers)

IT 124-38-9, Carbon dioxide, uses  
(supercrit.; addn. dispersion polymn. in fluid reaction  
medium using removable stabilizers)

REFERENCE COUNT: 2

REFERENCE(S): (1) Air Prod & Chem; EP 0814112 A 1997 HCAPLUS  
(2) Menciloglu Yusuf, Z; WO 9504085 A 1995  
HCAPLUS

L42 ANSWER 4 OF 17 HCAPLUS COPYRIGHT 2001 ACS

ACCESSION NUMBER: 1999:816229 HCAPLUS

DOCUMENT NUMBER: 132:108382

TITLE: Dispersion polymerization of methyl methacrylate  
in **supercritical carbon**  
**dioxide** with a monofunctional

AUTHOR(S): pseudo-graft stabilizer  
Christian, Paul; Howdle, Steven M.; Irvine,  
Derek J.

CORPORATE SOURCE: School of Chemistry, University of Nottingham,  
Nottingham, NG7 2RD, UK

SOURCE: Macromolecules (2000), 33(2), 237-239  
CODEN: MAMOBX; ISSN: 0024-9297

PUBLISHER: American Chemical Society

DOCUMENT TYPE: Journal


LANGUAGE: English

AB The polymn. of Me methacrylate (MMA) in **supercrit.**  
**CO2** (scCO2) was performed in the presence of Krytox 157FSL,  
a com. available carboxylic acid-terminated  
**perfluoropolyether**, as stabilizer. Fourier-transform IR  
(FTIR) spectroscopy was used to demonstrate an interaction between  
the **terminal acid group** of the stabilizer with  
MMA, and hence with PMMA. The samples were presented as thin liq.  
films of MMA, stabilizer, and various mixts. on CaF2 disks and  
mounted in transmission mode of the FTIR spectrometer. Krytox is an  
effective stabilizer for the free radical polymn. of MMA in scCO2.  
The interaction with PMMA is most likely via a H-bond between the  
C=O of the methacrylate moiety and the **terminal acid**  
**group** of the stabilizer. The terminal acid functionality is  
required for stabilization of the polymn. reaction.

IT 90317-74-1, Krytox 157FSL  
(stabilizer; dispersion polymn. of Me methacrylate in  
**supercrit. CO2** with monofunctional pseudo-graft  
fluoropolymer stabilizer)

RN 90317-74-1 HCAPLUS

CN Poly[oxy(trifluoro(trifluoromethyl)-1,2-ethanediyl)],  
.alpha.-(1-carboxy-1,2,2,2-tetrafluoroethyl)-.omega.-  
(heptafluoropropoxy)-(9CI) (CA INDEX NAME)



- CC 35-4 (Chemistry of Synthetic High Polymers)
- ST polymn methyl methacrylate **perfluoropolyether** stabilizer  
**supercrit carbon dioxide**; IR spectroscopy interaction stabilizer PMMA; polyoxyalkylene fluoro graft polymer intermediate PMMA prepn
- IT Polyoxyalkylenes, uses  
 (fluorine-contg., stabilizer; dispersion polymn. of Me methacrylate in **supercrit. CO2** with monofunctional pseudo-graft fluoropolymer stabilizer)
- IT Fluoropolymers, uses  
 (polyoxyalkylene-, stabilizer; dispersion polymn. of Me methacrylate in **supercrit. CO2** with monofunctional pseudo-graft fluoropolymer stabilizer)
- IT 9011-14-7P, PMMA  
 (dispersion polymn. of Me methacrylate in **supercrit. CO2** with monofunctional pseudo-graft fluoropolymer stabilizer)
- IT 90317-74-1, Krytox 157FSL  
 (stabilizer; dispersion polymn. of Me methacrylate in **supercrit. CO2** with monofunctional pseudo-graft fluoropolymer stabilizer)
- REFERENCE COUNT: 17
- REFERENCE(S): (2) Buback, M; J Supercrit Fluids 1995, V8, P119 HCAPLUS  
 (3) Canelas, D; Macromolecules 1997, V30, P5673 HCAPLUS  
 (5) Darr, J; Chem Rev 1999, V99, P495 HCAPLUS  
 (6) DeSimone, J; Science 1994, V265, P356 HCAPLUS  
 (7) Desimone, J; Science 1992, V257, P945 HCAPLUS
- ALL CITATIONS AVAILABLE IN THE RE FORMAT

L42 ANSWER 5 OF 17 HCAPLUS COPYRIGHT 2001 ACS

ACCESSION NUMBER: 1999:347680 HCAPLUS

DOCUMENT NUMBER: 131:116844

TITLE: **Supercritical CO2** as a solvent for polymeric **stone** protective materials

AUTHOR(S): Henon, F. E.; Camaiti, M.; Burke, A. L. C.; Carbonell, R. G.; DeSimone, J. M.; Piacenti, F.

CORPORATE SOURCE: Department of Chemical Engineering and Kenan Center for the Utilization of CO2 in


SOURCE: Manufacturing, North Carolina State University,  
Raleigh, NC, 27695-7905, USA  
J. Supercrit. Fluids (1999), 15(2), 173-179  
CODEN: JSFLEH; ISSN: 0896-8446  
PUBLISHER: Elsevier Science B.V.  
DOCUMENT TYPE: Journal  
LANGUAGE: English

AB The utilization of **CO2** as a potential solvent for fluoropolymers used for the protection of civil infrastructures (buildings, bridges, monuments, etc.) is of major environmental as well as economic importance. The cloud points of six **perfluoropolyethers** at different wt. concns. in **CO2** have been measured over a wide range of pressures. The results show that these fluorinated polymers are readily sol. in pure **CO2** (no cosolvent or surfactant needed) at temps. close to 30.degree.C and pressures below 210 bars. The solubilities of the different polymeric products are strongly depend on the polymer hydrogen content and mol. wt.

IT 124-38-9, **Carbon dioxide**, uses  
(**supercrit. carbon dioxide** as  
solvent for **perfluoropolyethers** used as **stone**  
protection materials)

RN 124-38-9 HCAPLUS

CN Carbon dioxide (8CI, 9CI) (CA INDEX NAME)



CC 36-7 (Physical Properties of Synthetic High Polymers)

ST **perfluoropolyether** protective coating **supercrit**  
solvent; **carbon dioxide supercrit**  
solvent fluoropolymer; **stone** protective coating  
**supercrit** solvent

IT **Polyethers**, uses  
(**perfluoro; supercrit. carbon**  
**dioxide** as solvent for **perfluoropolyethers** used  
as **stone** protection materials)

IT **Fluoropolymers**, uses  
(**polyether-; supercrit. carbon**  
**dioxide** as solvent for **perfluoropolyethers** used  
as **stone** protection materials)

IT **Stone (construction material)**  
(**supercrit. carbon dioxide** as  
solvent for **perfluoropolyethers** used as **stone**  
protection materials)

IT **Solvents**  
(**supercrit.; supercrit. carbon**  
**dioxide** as solvent for **perfluoropolyethers** used  
as **stone** protection materials)

IT **Coating materials**  
(weather-resistant; **supercrit. carbon**

dioxide as solvent for perfluoropolyethers used  
as stone protection materials)  
IT 124-38-9, Carbon dioxide, uses  
(supercrit. carbon dioxide as  
solvent for perfluoropolyethers used as stone  
protection materials)

REFERENCE COUNT: 42

REFERENCE(S):

- (1) Brady, J; Journal of Physical Chemistry  
1985, V89, P1813 HCAPLUS
  - (3) Cece, A; Journal of Physical Chemistry 1996,  
V100, P7435 HCAPLUS
  - (4) DeSimone, J; Science 1992, V257, P945  
HCAPLUS
  - (5) Diep, P; Journal of Physical Chemistry 1998,  
V102, P2231 HCAPLUS
  - (6) Enick, R; Journal of Supercritical Fluids  
1998, V13, P127 HCAPLUS
- ALL CITATIONS AVAILABLE IN THE RE FORMAT

L42 ANSWER 6 OF 17 HCAPLUS COPYRIGHT 2001 ACS

ACCESSION NUMBER: 1999:262197 HCAPLUS

DOCUMENT NUMBER: 130:298067

TITLE: Coating compositions and their application for  
protecting civil engineering infrastructure from  
pollution effects

INVENTOR(S): Carbonell, Ruben G.; Desimone, Joseph M.; Henon,  
Florence E.

PATENT ASSIGNEE(S): North Carolina State University, USA; The  
University of North Carolina At Chapel Hill

SOURCE: PCT Int. Appl., 20 pp.

CODEN: PIXXD2

DOCUMENT TYPE: Patent

LANGUAGE: English

FAMILY ACC. NUM. COUNT: 1

PATENT INFORMATION:

PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
WO 9919080	A1	19990422	WO 1998-US21175	19981008
W:	AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, HR, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, VZ, VN, YU, ZW, AM, AZ, BY, KG, KZ, MD, RU, TJ, TM			
RW:	GH, GM, KE, LS, MW, SD, SZ, UG, ZW, AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG			
US 6127000	A	20001003	US 1997-948733	19971010
AU 9910710	A1	19990503	AU 1999-10710	19981008
EP 1051264	A1	20001115	EP 1998-953303	19981008
R:	AT, BE, CH, DE, DK, ES, FR, GB, GR, IT, LI, LU, NL, SE, MC,			

PT, IE, FI  
 JP 11256093 A2 19990921 JP 1998-288957 19981012  
 PRIORITY APPLN. INFO.: US 1997-948733 A 19971010  
 WO 1998-US21175 W 19981008

AB The title sprayable coating compn. comprises **CO2** carrier and a fluorocarbon such as a **fluoropolyether** (preferably a **perfluoropolyether**) or a fluorocarbon elastomer, optionally having .gtoreq.1 **anchoring group** such as an **amide**.

IT **124-38-9, Carbon dioxide**, uses ((**supercrit.**) solvent, fluoropolymer soly. in; coating compns. for protecting civil engineering infrastructure from pollution effects)

RN **124-38-9 HCAPLUS**

CN **Carbon dioxide (8CI, 9CI) (CA INDEX NAME)**

O=C=O

IC ICM B05D001-02  
 ICS B05D003-02

CC 42-10 (Coatings, Inks, and Related Products)  
 Section cross-reference(s): 58

ST **fluoropolyether carbon dioxide** coating  
**building material**; fluoro rubber **carbon dioxide** coating **building material**

IT **Bricks**  
**Cement (construction material)**  
**Ceramics**  
**Concrete**  
 (coating compns. for protecting civil engineering infrastructure from pollution effects)

IT **Stone (construction material)**  
 (coating compns. for protecting civil engineering infrastructure from pollution effects)

IT **Coatings**  
 (fluoropolymer in **carbon dioxide**; coating compns. for protecting civil engineering infrastructure from pollution effects)

IT **Spray coating**  
 (of fluoropolymer in **supercrit. carbon dioxide** onto **building material**)

IT **Polyethers**, uses  
 (**perfluoro**; coating compns. for protecting civil engineering infrastructure from pollution effects)

IT **Fluoropolymers**, uses  
 (**polyether-**; coating compns. for protecting civil engineering infrastructure from pollution effects)

IT **124-38-9, Carbon dioxide**, uses  
 ((**supercrit.**) solvent, fluoropolymer soly. in; coating compns. for protecting civil engineering infrastructure from

pollution effects)

REFERENCE COUNT: 2

REFERENCE(S): (1) Desimone; US 5496901 A 1996 HCAPLUS  
(2) Piacenti; US 4745009 A 1988 HCAPLUS

L42 ANSWER 7 OF 17 HCAPLUS COPYRIGHT 2001 ACS

ACCESSION NUMBER: 1998:253836 HCAPLUS

DOCUMENT NUMBER: 128:258003

TITLE: Gas and water vapor transport through polymer based protective materials for **stone** monuments. Fluorinated polyurethanes

AUTHOR(S): Antonucci, V.; Mastrangeli, C.; Mensitieri, G.; Del Nobile, M. A.; Nicolais, L.

CORPORATE SOURCE: Dep. Mater. Production Eng., Univ. Naples 'Federico II', Naples, 80125, Italy

SOURCE: Mater. Struct. (1998), 31(206), 104-110  
CODEN: MASTED; ISSN: 1359-5997

PUBLISHER: RILEM Publications

DOCUMENT TYPE: Journal

LANGUAGE: English

AB Oxygen, **carbon dioxide** and water vapor transport properties were investigated for a new class of polymers, fluorinated polyurethanes, which were recently proposed as a protective material for **stone** monuments. They consist of block copolymers made of hydrophilic polyurethane and hydrophobic perfluoropolymer blocks. Properties of these copolymers are expected to be strongly related to the relative amts. of these two blocks. Three different types of fluorinated polyurethane copolymers were considered in order to assess the effect of chem. compn. and phys. morphol. on mass transport properties. In particular, sorption and permeation expts. were performed at 30.degree.C to evaluate permeabilities, diffusivities and solubilities. The anal. of the effect of chem. compn. on transport properties can give useful selection criteria to tailor the material to be used as a protective.

IT 124-38-9, **Carbon dioxide**, processes

(gas and water vapor transport through fluorinated polyurethanes)

RN 124-38-9 HCAPLUS

CN Carbon dioxide (8CI, 9CI) (CA INDEX NAME)

O=C=O

CC 37-5 (Plastics Manufacture and Processing)

ST fluorinated polyurethane gas water vapor transport; block copolymer polyurethane permeation sorption; oxygen transport fluorinated polyurethane; **carbon dioxide** transport fluorinated polyurethane; sorption gas water fluorinated polyurethane; permeation gas water fluorinated polyurethane

IT **Fluoropolymers**, properties

(polyether-polyurethane-, block; gas and water vapor

transport through fluorinated polyurethanes)  
IT 124-38-9, Carbon dioxide, processes  
7782-44-7, Oxygen, processes  
(gas and water vapor transport through fluorinated polyurethanes)

L42 ANSWER 8 OF 17 HCAPLUS COPYRIGHT 2001 ACS

ACCESSION NUMBER: 1998:148768 HCAPLUS

DOCUMENT NUMBER: 128:193369

TITLE: Nanotechnological method to control the  
molecular weight cut-off and/or pore diameter of  
organic-inorganic composite membrane

AUTHOR(S): Okazaki, I.; Ohya, H.; Semenova, S. I.; Kikuchi,  
S.; Aihara, M.; Negishi, Y.

CORPORATE SOURCE: Department of Material Science and Chemical  
Engineering, Yokohama National University, 79-5  
Tokiwadai Hodogaya-ku, Yokohama, Japan

SOURCE: J. Membr. Sci. (1998), 141(1), 65-74

CODEN: JMESDO; ISSN: 0376-7388

PUBLISHER: Elsevier Science B.V.

DOCUMENT TYPE: Journal

LANGUAGE: English

AB Polyimide-alumina composite membranes were fabricated by the  
nanotechnol. copolymn. method of co-polymer which has a const.  
repeating unit chem. bound by primer on the wall and/or surface of  
the porous **ceramic** support. By changing the no. of  
repeating unit (n) in the polymer, the fabricated pyromellitic  
dianhydride (PMDA)-diaminodiphenyl ether (ODA) composite membranes  
have a sepn. factor  $\alpha_{\text{CO}_2/\text{CH}_4}$  in the range 1.0-6.4  
and mol. wt. cut-off (MWCO) 400-4000. As for the composite  
membranes of n = 20, the sepn. factor  $\alpha_{\text{CO}_2/\text{CH}_4}$  of  
the 4,4'-(hexafluoroisopropylidene)-diphthalic anhydride  
(6FDA)-diaminodiphenyl ether (ODA) composite membrane was approx.  
1.6 times larger than that of the PMDA-ODA composite membranes, and  
these values were 7.5 and 4.7 at 323 K, resp. With the increase of  
temp., the sepn. factor decreased, and the value obtained was 4.8 at  
423 K. The pure gas permeances through the carbon membrane  
(PMDA-ODA: n = 20) was approx. 75-260 times larger than the values  
through the PMDA-ODA (n = 20) composite membranes. However, this  
membrane did not show any gas sepn. ability.

IT 124-38-9, Carbon dioxide, processes

(sepn. of, from methane; nanotechnol. method to control mol. wt.  
cut-off and/or pore diam. of org.-inorg. polyimide-alumina  
composite membranes for)

RN 124-38-9 HCAPLUS

CN Carbon dioxide (8CI, 9CI) (CA INDEX NAME)

O=C=O

CC 38-3 (Plastics Fabrication and Uses)  
Section cross-reference(s): 57



- IT **Fluoropolymers**, uses  
(polyether-polyimide-, composite membrane; nanotechnol. method to control mol. wt. cut-off and/or pore diam. of org.-inorg. polyimide-alumina composite membranes)
- IT 74-82-8, Methane, processes  
(sepn. of, from **carbon dioxide**; nanotechnol. method to control mol. wt. cut-off and/or pore diam. of org.-inorg. polyimide-alumina composite membranes)
- IT **124-38-9, Carbon dioxide**, processes  
(sepn. of, from methane; nanotechnol. method to control mol. wt. cut-off and/or pore diam. of org.-inorg. polyimide-alumina composite membranes for)

L42 ANSWER 9 OF 17 HCAPLUS COPYRIGHT 2001 ACS

ACCESSION NUMBER: 1997:425993 HCAPLUS

DOCUMENT NUMBER: 127:136197

TITLE: Chelating agents for extraction of metals in **supercritical carbon dioxide**

INVENTOR(S): Beckman, Eric J.; Russell, Alan J.

PATENT ASSIGNEE(S): University of Pittsburgh, USA

SOURCE: U.S., 21 pp.  
CODEN: USXXAM

DOCUMENT TYPE: Patent

LANGUAGE: English

FAMILY ACC. NUM. COUNT: 4


PATENT INFORMATION:

PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
US 5641887	A	19970624	US 1994-223105	19940401
US 5872257	A	19990216	US 1997-831999	19970401
US 6183815	B1	20010206	US 1999-250537	19990216


PRIORITY APPLN. INFO.: US 1994-223105 A2 19940401  
US 1997-831999 A2 19970401

- AB The title agents suitable for forming coordinated complexes with a metal in liq. and **supercritical CO2** contain covalently bonded (i) a bispicolylamino group, (ii) a non-electron withdrawing spacer group selected (CH2)x and (iii) a **CO2**-sol. functional group selected from (CF2CF2O)x(CF2O)x and [CF2CF(CF3)O]x, wherein x (.gtoreq.3) is selected to minimize the electron withdrawing effect of the **CO2**-sol. functional group and to achieve a chelating agent soly. .gtoreq.10-3 g/g-**CO2**. Also disclosed is a method of extg. a metal from a matrix contg. at least one other material and the metal using such **CO2**-sol. chelating agents. Krytox 157FSL was treated with thionyl chloride to convert into acid chloride and treated with picolylamine, dipicolylamine, dimercaptopropanol, etc. to obtain chelating agents suitable for extg. Ni, Pb, etc.
- IT **106441-57-0DP**, Krytox 157FSL, chelating group-contg. derivs. (chelating agents for extn. of metals in **supercrit. carbon dioxide**)

RN 106441-57-0 HCAPLUS  
 IT 124-38-9, **Carbon dioxide**, uses  
 (chelating agents for extn. of metals in **supercrit.**  
**carbon dioxide**)  
 RN 124-38-9 HCAPLUS  
 CN Carbon dioxide (8CI, 9CI) (CA INDEX NAME)



IT 25038-02-2DP, Poly(hexafluoropropylene oxide),  
**carboxy-terminated**, chelating **group**  
 -contg.  
 (chelating agents for extn. of metals in **supercrit.**  
**carbon dioxide**)  
 RN 25038-02-2 HCAPLUS  
 CN Oxirane, trifluoro(trifluoromethyl)-, homopolymer (9CI) (CA INDEX  
 NAME)  
 CM 1  
 CRN 428-59-1  
 CMF C3 F6 O



IC ICM C07D401-06  
 NCL 546026200  
 CC 35-8 (Chemistry of Synthetic High Polymers)  
 Section cross-reference(s): 60  
 IT Chelating agents  
 Extraction  
 (chelating agents for extn. of metals in **supercrit.**  
**carbon dioxide**)  
 IT Polysiloxanes, preparation  
 (chelating group-contg.; chelating agents for extn. of metals in  
**supercrit. carbon dioxide**)  
 IT Polyoxyalkylenes, preparation  
 (perfluoro, **carboxy-terminated**, chelating  
**group**-contg.; chelating agents for extn. of metals in  
**supercrit. carbon dioxide**)  
 IT Fluoropolymers, preparation  
 (polyoxyalkylene-, **carboxy-terminated**,  
 chelating **group**-contg.; chelating agents for extn. of  
 metals in **supercrit. carbon dioxide**)

- )
- IT 59-52-9DP, 2,3-Dithio-1-propanol, reaction products with carboxy-terminated **perfluoropolyethers** 75-15-0DP, Carbon disulfide, reaction products with dimethylethylenediamine and carboxy-terminated **perfluoropolyethers** 93-62-9DP, 2-Hydroxyethyliminodiacetic acid, reaction products with carboxy-terminated **perfluoropolyethers**, hydrolyzed 106-92-3DP, reaction products with Me hydrogen siloxane and picolylamine 110-70-3DP, reaction products with carbon disulfide and carboxy-terminated **perfluoropolyethers** 154-42-7DP, reaction products with carboxy-terminated **perfluoropolyethers** 452-06-2DP, 1H-Purin-2-amine, reaction products with carboxy-terminated **perfluoropolyethers** 1656-94-6DP, reaction products with carboxy-terminated **perfluoropolyethers** 3731-52-0DP, 3-Picolyl amine, reaction products with carboxy-terminated **perfluoropolyethers** 10025-87-3DP, Phosphorus oxychloride, reaction products with carboxy-terminated **perfluoropolyethers**, hydrolyzed 106441-57-0DP, Krytox 157FSL, chelating group-contg. derivs. 156118-35-3DP, Dimethylsilanediol-methylsilanediol copolymer, reaction products with allyl glycidyl ether and picolylamine (chelating agents for extn. of metals in **supercrit. carbon dioxide**)
- IT 124-38-9, Carbon dioxide, uses (chelating agents for extn. of metals in **supercrit. carbon dioxide**)
- IT 7439-92-1P, Lead, preparation 7440-02-0P, Nickel, preparation 25038-02-2DP, Poly(hexafluoropropylene oxide), carboxy-terminated, chelating group -contg. (chelating agents for extn. of metals in **supercrit. carbon dioxide**)
- IT 7719-09-7, Thionyl chloride (chelating agents for extn. of metals in **supercrit. carbon dioxide**)

L42 ANSWER 10 OF 17 HCAPLUS COPYRIGHT 2001 ACS

ACCESSION NUMBER: 1997:113146 HCAPLUS

DOCUMENT NUMBER: 126:104490

TITLE: Dispersion Polymerization of Methyl Methacrylate in **Supercritical CO2**

AUTHOR(S): Lepilleur, Carole; Beckman, Eric J.

CORPORATE SOURCE: Chemical Engineering Department, University of Pittsburgh, Pittsburgh, PA, 15261, USA

SOURCE: Macromolecules (1997), 30(4), 745-756  
CODEN: MAMOBX; ISSN: 0024-9297

PUBLISHER: American Chemical Society

DOCUMENT TYPE: Journal

LANGUAGE: English


AB A series of graft copolymers, poly(Me methacrylate-co-hydroxyethyl methacrylate)-g-poly(perfluoropropylene oxide), was synthesized for application as stabilizers in the dispersion polymn. of Me

methacrylate in **supercrit. carbon dioxide**. The backbone, poly(Me methacrylate-co-hydroxyethyl methacrylate), is effectively insol. in **carbon dioxide** and the grafted chains, poly(perfluoropropylene oxide), are completely miscible in **carbon dioxide** at moderate pressures. The effect of mol. architecture on polymn. rate and PMMA particle size was evaluated by varying the mol. wt. of the **anchor group** (backbone of the copolymer), mol. wt. of the **CO<sub>2</sub>**-sol. graft chain, and graft chain d. The efficiency of the graft copolymers as dispersants was demonstrated as micron-size polymer beads of mol. wt. greater than 100,000 were produced. A careful balance between **anchor group** size (backbone length) and amt. of sol. component (either graft chain length or graft chain d.) is necessary but not sufficient to achieve adequate stabilization. The distribution of the sol. component along the **anchor group** is also important. Furthermore, the backbone mol. wt. was shown as the key component for stabilization, provided that enough **CO<sub>2</sub>**-philic component has been included to ensure soly.

IT 124-38-9, **Carbon dioxide**, uses  
(stabilizer for use in dispersion polymn. of Me methacrylate in **supercrit. carbon dioxide**)

RN 124-38-9 HCAPLUS

CN Carbon dioxide (8CI, 9CI) (CA INDEX NAME)



IT 185997-25-5P, 2-Hydroxyethyl methacrylate-methyl methacrylate-perfluoropropylene oxide graft polymer  
(stabilizer; prepn. and use in dispersion polymn. of Me methacrylate in **supercrit. carbon dioxide**)


RN 185997-25-5 HCAPLUS

CN 2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, polymer with methyl 2-methyl-2-propenoate and trifluoro(trifluoromethyl)oxirane, graft (9CI) (CA INDEX NAME)

CM 1

CRN 868-77-9


CMF C6 H10 O3



CM 2

CRN 428-59-1


CMF C3 F6 O



CM 3

CRN 80-62-6

CMF C5 H8 O2



- CC 35-4 (Chemistry of Synthetic High Polymers)  
 ST dispersion polymn methyl methacrylate **carbon dioxide**; stabilizer dispersion polymn methyl methacrylate  
 IT Polymerization  
     (dispersions; stabilizer for use in dispersion polymn. of Me methacrylate in **supercrit. carbon dioxide**)  
 IT 124-38-9, **Carbon dioxide**, uses  
     (stabilizer for use in dispersion polymn. of Me methacrylate in **supercrit. carbon dioxide**)  
 IT 9011-14-7P, Poly(methyl methacrylate)  
     (stabilizer for use in dispersion polymn. of Me methacrylate in **supercrit. carbon dioxide**)  
 IT 185997-25-5P, 2-Hydroxyethyl methacrylate-methyl methacrylate-perfluoropropylene oxide graft polymer  
     (stabilizer; prepn. and use in dispersion polymn. of Me methacrylate in **supercrit. carbon dioxide**)

L42 ANSWER 11 OF 17 HCAPLUS COPYRIGHT 2001 ACS  
 ACCESSION NUMBER: 1997:21239 HCAPLUS  
 DOCUMENT NUMBER: 126:53871  
 TITLE: Cleaning and treating a micromechanical device  
 INVENTOR(S): Wallace, Robert M.; Douglas, Monte A.  
 PATENT ASSIGNEE(S): Texas Instruments Incorporated, USA  
 SOURCE: Eur. Pat. Appl., 11 pp.  
 CODEN: EPXXDW

DOCUMENT TYPE: Patent  
 LANGUAGE: English  
 FAMILY ACC. NUM. COUNT: 1  
 PATENT INFORMATION:

PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
EP 746013	A2	19961204	EP 1996-108733	19960531
EP 746013	A3	19991027		

R: DE, FR, GB, IT, NL

PRIORITY APPLN. INFO.: US 1995-455466 19950531

AB A method of cleaning and treating a device, including those of the micromech. and semiconductor types, is described. The surface of a device, such as the landing electrode of a digital micromirror device, is 1st cleaned with a **supercrit.** fluid (**SCF**) in a chamber to remove sol. chem. compds., and then kept in the **SCF** chamber until and during the subsequent passivation step. Passivating agents including perfluorodecanoic acid and **perfluoropolyether** are suitable for the present invention. By keeping the device in the **SCF** chamber, and without exposing the device to, for instance, the ambient of a clean room, org. and inorg. contaminants cannot be deposited on the cleaned surface prior to the passivation step. The present invention derives tech. advantages by providing an improved passivated surface that is suited to extend the useful operation life of devices, including those of the micromech. type, reducing stiction forces between contacting elements such as a mirror and its landing electrode. The present invention is also suitable for cleaning and passivating other surfaces, including those of semiconductor wafers and hard disks.

IT 124-38-9, **Carbon dioxide**, processes  
 (cleaning agent for micromech. devices)

RN 124-38-9 HCAPLUS

CN Carbon dioxide (8CI, 9CI) (CA INDEX NAME)

O=C=O

IC ICM H01L021-306

ICS G02B026-08

CC 76-3 (Electric Phenomena)

Section cross-reference(s): 73

IT **Coating process**

(formation of protective films on micromech. devices)

IT **Polyethers**, processes

(**perfluoro**; passivating agents for micromech. devices)

IT **Fluoropolymers**

(**polyether**-; passivating agents for micromech. devices)


IT 124-38-9, **Carbon dioxide**, processes

(cleaning agent for micromech. devices)

L42 ANSWER 12 OF 17 HCAPLUS COPYRIGHT 2001 ACS  
ACCESSION NUMBER: 1996:462234 HCAPLUS  
DOCUMENT NUMBER: 125:114490  
TITLE: Preparation of **fluorinated polyether** containing organic free radical compound as lubricating oil for magnetic recording medium  
INVENTOR(S): Yamana, Masayuki; Honda, Yoshitaka  
PATENT ASSIGNEE(S): Daikin Industries, Ltd., Japan  
SOURCE: PCT Int. Appl., 42 pp.  
CODEN: PIXXD2  
DOCUMENT TYPE: Patent  
LANGUAGE: Japanese  
FAMILY ACC. NUM. COUNT: 1  
PATENT INFORMATION:

PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
-----	----	-----	-----	-----
WO 9611905	A1	19960425	WO 1995-JP2084	19951012
W: JP, US				
RW: AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE				
EP 786451	A1	19970730	EP 1995-934279	19951012
R: DE, FR, GB, IT				
US 5965496	A	19991012	US 1997-817440	19970523
PRIORITY APPLN. INFO.:			JP 1994-248148	19941013
			WO 1995-JP2084	19951012

GI



AB A **fluorinated polyether** compd. represented by the following general formula X-(Rf1)-(CF2)x-(CH2)y-(CHRCH2)z1-Y1-Z1 (I) or Z2-Y2-(CH2CHR)z2-(CH2)y-(CF2)x-(Rf2)-(CF2)x-(CH2)y-(CHRCH2)z3-Y3-Z3 (II) [Rf1 and Rf2 represent each a **fluorinated polyether** group, **perfluoroalkyl** group or perfluoroalkenyl group; X = H, F, Cl; Y1, Y2, Y3 = O, CO2, CONH; x, y = 0-10; z1, z2, z3 = 0,1; R = H, OH; provided that when R = OH, Y1, Y2, and Y3 = O; Z1, Z2 and Z3 represent each a member selected from among groups contg. org. free radicals represented by formulas Tempol (Q), DPPH (3- or 4-Q1), VDZ (3- or 4-Q2)], which firmly adheres in a thin film to the surface of carbon, amorphous carbon, graphite, **ceramic**, or metals and show good lubricating property and excellent durability, is prepd. A lubricating oil for magnetic recording medium contains said lubricating oil I or II as the essential ingredient. Thus, 100 g F(CF2CF2CF2O)nCF2CF2COF (n = av. 25) was dissolved in 200 mL perfluorohexane, treated with 20 g 4-hydroxy-2,2,6,6-tetramethylpiperidine-1-oxide under stirring, and heated at 60.degree. for 100 h to give the title compd. (III) (96 g). A hard disk having a carbon top layer was immersed in a 0.1 wt.% soln. of III, taken out, and heated at 80.degree. for 1 h to form a lubricating film (20 .ANG.). The disk showed friction coefficient of .ltoreq.0.5 after 50,000 working cycles in a CSS tester.

IC ICM C07C243-00

ICS C07D211-94; C07D257-02; C10M105-56; C10M107-44; G11B005-71

ICI C10N040-18

CC 27-16 (Heterocyclic Compounds (One Hetero Atom))



- Section cross-reference(s): 74
- ST **fluorinated polyether** contg org radical prepn;  
lubricating oil magnetic recording medium
- IT Lubricants  
(prepn. of **fluorinated polyether** contg. org.  
free redial compd. as lubricating oil for magnetic recording  
medium)
- IT Fluoropolymers  
(prepn. of **fluorinated polyether** contg. org.  
free redial compd. as lubricating oil for magnetic recording  
medium)
- IT Polyethers, preparation  
Polyoxyalkylenes, preparation  
(fluorine-contg., prepn. of **fluorinated  
polyether** contg. org. free redial compd. as lubricating  
oil for magnetic recording medium)
- IT Recording materials  
(magnetic, prepn. of **fluorinated polyether**  
contg. org. free redial compd. as lubricating oil for magnetic  
recording medium)
- IT **Fluoropolymers**  
(**polyether-**, prepn. of **fluorinated  
polyether** contg. org. free redial compd. as lubricating  
oil for magnetic recording medium)
- IT Fluoropolymers  
(polyoxyalkylene-, prepn. of **fluorinated  
polyether** contg. org. free redial compd. as lubricating  
oil for magnetic recording medium)
- IT 179167-24-9, 2-(4-Hydroxyphenyl)-2-phenyl-1-picrylhydrazine  
(fluoropolymer polyoxyalkylenes; prepn. of **fluorinated  
polyether** contg. org. free redial compd. as lubricating  
oil for magnetic recording medium)
- IT 41925-33-1 133921-38-7  
(fluoropolymer polyoxyalkylenes; prepn. of **fluorinated  
polyether** contg. org. free redial compd. as lubricating  
oil for magnetic recording medium)
- IT 179167-18-1P 179167-19-2P 179167-20-5P 179167-21-6P  
(prepn. of **fluorinated polyether** contg. org.  
free redial compd. as lubricating oil for magnetic recording  
medium)
- IT 2226-96-2, 4-Hydroxy-2,2,6,6-Tetramethyl-1-piperidinyloxy  
3225-24-9 14691-88-4 127494-88-6 179167-23-8  
(prepn. of **fluorinated polyether** contg. org.  
free redial compd. as lubricating oil for magnetic recording  
medium)

L42 ANSWER 13 OF 17 HCAPLUS COPYRIGHT 2001 ACS

ACCESSION NUMBER: 1995:315718 HCAPLUS

DOCUMENT NUMBER: 122:83131

TITLE: Silica-Treated **Ceramic** Substrates for  
Formation of Polymer-**Ceramic** Composite  
Membranes

AUTHOR(S): Moaddeb, Maryam; Koros, William J.  
 CORPORATE SOURCE: Department of Chemical Engineering, University  
 of Texas, Austin, TX, 78712, USA  
 SOURCE: Ind. Eng. Chem. Res. (1995), 34(1), 263-74  
 CODEN: IECRED; ISSN: 0888-5885  
 DOCUMENT TYPE: Journal  
 LANGUAGE: English

AB Fabrication of composite membranes from a highly porous substrate and a thin polymeric permselective layer allows achieving both high flux and selectivity in a single structure. In practice, formation of such composites is difficult due to the presence of large pores on the surface of highly permeable substrates. A novel approach to the formation of composite membranes was examd. in this work to avoid this difficulty with large, hard-to-coat pores. Anopore microporous aluminum oxide membranes with 2000 .ANG. pores were used as model systems and were treated with 100 .ANG. spherical colloidal silica particles to reduce their pore diam. while maintaining low flow resistance through them. The silica-treated **ceramics** were then used as substrates for formation of thin defect-free polymer-**ceramic** composite membranes by a soln.-coating method. A polycarbonate, 2 fluoropolymer-polyimides, and a **fluoropolymer-polyether-polysulfone** were used as the polymer coatings. The treatment protocols, characterization of the treated substrates, and gas permeation results for the composites formed are discussed.

IT 124-38-9, **Carbon dioxide**, properties  
 (polymer-**ceramic** composite membranes for gas sepn.  
 prepd. from silica-treated **ceramic** substrates coated  
 with polymers)

RN 124-38-9 HCAPLUS

CN Carbon dioxide (8CI, 9CI) (CA INDEX NAME)

O=C=O

CC 38-3 (Plastics Fabrication and Uses)

Section cross-reference(s): 47, 57

ST **ceramic** substrate silica polymer layer membrane; polyether  
**ceramic** composite membrane; polysulfone **ceramic**  
 composite membrane; polyimide **ceramic** composite membrane;  
 fluoropolymer **ceramic** composite membrane; polycarbonate  
**ceramic** composite membrane; gas sepn polymer **ceramic**  
 composite membrane; alumina silica polymer composite membrane

IT Polymer morphology  
 (in polymer-**ceramic** composite membranes for gas sepn.  
 prepd. from silica-treated **ceramic** substrates coated  
 with polymers)

IT **Ceramic** materials and wares  
 Membranes

(polymer-**ceramic** composite membranes for gas sepn.  
 prepd. from silica-treated **ceramic** substrates coated

- with polymers)
- IT Polycarbonates, uses  
(polymer-**ceramic** composite membranes for gas sepn.  
prepd. from silica-treated **ceramic** substrates coated  
with polymers)
- IT Pore  
(pore size in polymer-**ceramic** composite membranes for  
gas sepn. prepd. from silica-treated **ceramic** substrates  
coated with polymers)
- IT Polyimides, uses  
(fluorine-contg., polymer-**ceramic** composite membranes  
for gas sepn. prepd. from silica-treated **ceramic**  
substrates coated with polymers)
- IT Polysulfones, uses  
(polyether-, fluorine-contg., polymer-**ceramic** composite  
membranes for gas sepn. prepd. from silica-treated  
**ceramic** substrates coated with polymers)
- IT Fluoropolymers  
(polyether-polysulfone-, polymer-**ceramic**  
composite membranes for gas sepn. prepd. from silica-treated  
**ceramic** substrates coated with polymers)
- IT Fluoropolymers  
(polyimide-, polymer-**ceramic** composite membranes for  
gas sepn. prepd. from silica-treated **ceramic** substrates  
coated with polymers)
- IT Polyethers, uses  
(polysulfone-, fluorine-contg., polymer-**ceramic**  
composite membranes for gas sepn. prepd. from silica-treated  
**ceramic** substrates coated with polymers)
- IT 24936-68-3P, Bisphenol A-carbonic acid copolymer, sru, uses  
25037-45-0P, Bisphenol A-carbonic acid copolymer 57138-86-0P  
57153-28-3P 111343-89-6P 111367-14-7P 140659-80-9P  
(polymer-**ceramic** composite membranes for gas sepn.  
prepd. from silica-treated **ceramic** substrates coated  
with polymers)
- IT 124-38-9, Carbon dioxide, properties  
7440-59-7, Helium, properties 7727-37-9, Nitrogen, properties  
7782-44-7, Oxygen, properties  
(polymer-**ceramic** composite membranes for gas sepn.  
prepd. from silica-treated **ceramic** substrates coated  
with polymers)
- IT 7631-86-9P, Silica, uses  
(silica-treated **ceramic** substrates for formation of  
polymer-**ceramic** composite membranes for gas sepn.)
- IT 1344-28-1P, Anopore, uses  
(substrate; silica-treated **ceramic** substrates for  
formation of polymer-**ceramic** composite membranes for  
gas sepn.)

TITLE: Inverse emulsion polymerization of acrylamide in **supercritical carbon dioxide**. [Erratum to document cited in CA120:55125]

AUTHOR(S): Adamsky, F. A.; Beckman, E. J.

CORPORATE SOURCE: Dep. Chem. Eng., Univ. Pittsburgh, Pittsburgh, PA, 15261, USA

SOURCE: Macromolecules (1994), 27(18), 5238  
CODEN: MAMOBX; ISSN: 0024-9297

DOCUMENT TYPE: Journal


LANGUAGE: English

AB The errors were not reflected in the abstr. or the index entries.

IT 124-38-9, **Carbon dioxide**, reactions  
(inverse emulsion polymn. of acrylamide in (Erratum))

RN 124-38-9 HCAPLUS


CN Carbon dioxide (8CI, 9CI) (CA INDEX NAME)



IT 90999-75-0P  
(prepn. and amidation of (Erratum))

RN 90999-75-0 HCAPLUS


CN Poly[oxy[trifluoro(trifluoromethyl)-1,2-ethanediyl]],  
.alpha.-[1-(chlorocarbonyl)-1,2,2,2-tetrafluoroethyl]-.omega.-  
(heptafluoropropoxy)- (9CI) (CA INDEX NAME)



IT 53789-69-8P  
(prepn. of, for surfactants for inverse emulsion polymn. of  
acrylamide in **supercrit. carbon dioxide** (Erratum))

RN 53789-69-8 HCAPLUS

CN Poly[oxy[trifluoro(trifluoromethyl)-1,2-ethanediyl]],  
.alpha.-[1-(aminocarbonyl)-1,2,2,2-tetrafluoroethyl]-.omega.-  
(heptafluoropropoxy)- (9CI) (CA INDEX NAME)




IT 90317-74-1

(reaction with thionyl chloride of (Erratum))

RN 90317-74-1 HCAPLUS

CN Poly[oxy[trifluoro(trifluoromethyl)-1,2-ethanediyl]],  
 .alpha.-(1-carboxy-1,2,2,2-tetrafluoroethyl)-.omega.-  
 (heptafluoropropoxy)-(9CI) (CA INDEX NAME)



IT 25038-02-2DP, Hexafluoropropylene oxide homopolymer,  
 amide group-terminated

(surfactants, for inverse emulsion polymn. of acrylamide in  
 supercrit. carbon dioxide (Erratum))


RN 25038-02-2 HCAPLUS

CN Oxirane, trifluoro(trifluoromethyl)-, homopolymer (9CI) (CA INDEX  
 NAME)

CM 1

CRN 428-59-1

CMF C3 F6 O



CC 35-4 (Chemistry of Synthetic High Polymers)

Section cross-reference(s): 46

ST erratum inverse emulsion polymn acrylamide surfactant; inverse  
 emulsion polymn acrylamide surfactant erratum; **supercrit**  
**carbon dioxide** acrylamide polymn erratum

IT Surfactants

- (fluorinated, prepn. of, for inverse emulsion polymn. of acrylamide in **supercrit. carbon dioxide** (Erratum))
- IT Polymerization  
(inverse emulsion, of acrylamide in **supercrit. carbon dioxide**, fluorinated surfactant for (Erratum))
- IT 124-38-9, **Carbon dioxide**, reactions  
(inverse emulsion polymn. of acrylamide in (Erratum))
- IT 90999-75-0P  
(prepn. and amidation of (Erratum))
- IT 53789-69-8P  
(prepn. of, for surfactants for inverse emulsion polymn. of acrylamide in **supercrit. carbon dioxide** (Erratum))
- IT 9003-05-8P  
(prepn. of, in inverse emulsion in **supercrit. carbon dioxide**, fluorinated surfactant for (Erratum))
- IT 90317-74-1  
(reaction with thionyl chloride of (Erratum))
- IT 25038-02-2DP, Hexafluoropropylene oxide homopolymer, **amide group-terminated**  
(surfactants, for inverse emulsion polymn. of acrylamide in **supercrit. carbon dioxide** (Erratum))

L42 ANSWER 15 OF 17 HCAPLUS COPYRIGHT 2001 ACS

ACCESSION NUMBER: 1994:55125 HCAPLUS

DOCUMENT NUMBER: 120:55125

TITLE: Inverse emulsion polymerization of acrylamide in **supercritical carbon dioxide**

AUTHOR(S): Adamsky, F. A.; Beckman, E. J.

CORPORATE SOURCE: Dep. Chem. Eng., Univ. Pittsburgh, Pittsburgh, PA, 15261, USA

SOURCE: Macromolecules (1994), 27(1), 312-14  
CODEN: MAMOBX; ISSN: 0024-9297

DOCUMENT TYPE: Journal


LANGUAGE: English

AB Inverse emulsion polymn. of acrylamide was performed using **supercrit. CO2** as the continuous phase to produce ultra-high mol.-wt. linear homopolymer. A new surfactant, highly sol. in **supercrit. CO2**, was synthesized to create the inverse emulsions. Data are presented for both surfactant and homopolymer characterization.

IT 124-38-9, **Carbon dioxide**, reactions  
(inverse emulsion polymn. of acrylamide in)

RN 124-38-9 HCAPLUS

CN Carbon dioxide (8CI, 9CI) (CA INDEX NAME)




IT 90999-75-0P

(prepn. and amidation of)

RN 90999-75-0 HCAPLUS

CN Poly[oxy(trifluoro(trifluoromethyl)-1,2-ethanediyl)],  
.alpha.-[1-(chlorocarbonyl)-1,2,2,2-tetrafluoroethyl]-.omega.-  
(heptafluoropropoxy) - (9CI) (CA INDEX NAME)




IT 53789-69-8P

(prepn. of, for surfactants for inverse emulsion polymn. of  
acrylamide in **supercrit. carbon**  
**dioxide**)

RN 53789-69-8 HCAPLUS

CN Poly[oxy(trifluoro(trifluoromethyl)-1,2-ethanediyl)],  
.alpha.-[1-(aminocarbonyl)-1,2,2,2-tetrafluoroethyl]-.omega.-  
(heptafluoropropoxy) - (9CI) (CA INDEX NAME)




IT 90317-74-1

(reaction with thionyl chloride of)

RN 90317-74-1 HCAPLUS

CN Poly[oxy(trifluoro(trifluoromethyl)-1,2-ethanediyl)],  
.alpha.-[1-carboxy-1,2,2,2-tetrafluoroethyl]-.omega.-  
(heptafluoropropoxy) - (9CI) (CA INDEX NAME)



IT 25038-02-2D, Hexafluoropropylene oxide homopolymer,  
amide group-terminated  
(surfactants, for inverse emulsion polymn. of acrylamide in  
**supercrit. carbon dioxide**)


RN 25038-02-2 HCAPLUS

CN Oxirane, trifluoro(trifluoromethyl)-, homopolymer (9CI) (CA INDEX  
NAME)

CM 1

CRN 428-59-1

CMF C3 F6 O



CC 35-4 (Chemistry of Synthetic High Polymers)  
Section cross-reference(s): 46

ST inverse emulsion polymn acrylamide surfactant; **supercrit  
carbon dioxide** acrylamide polymn

IT Surfactants  
(fluorinated; prepn. of, for inverse emulsion polymn. of  
acrylamide in **supercrit. carbon  
dioxide**)

IT Polymerization  
(inverse emulsion, of acrylamide in **supercrit.  
carbon dioxide**, fluorinated surfactant for)

IT 124-38-9, **Carbon dioxide**, reactions  
(inverse emulsion polymn. of acrylamide in)

IT 90999-75-0P  
(prepn. and amidation of)

IT 53789-69-8P  
(prepn. of, for surfactants for inverse emulsion polymn. of  
acrylamide in **supercrit. carbon  
dioxide**)

IT 9003-05-8P, Polyacrylamide  
(prepn. of, in inverse emulsion in **supercrit.  
carbon dioxide**, fluorinated surfactant for)

IT 90317-74-1



(reaction with thionyl chloride of)  
 IT 25038-02-2D, Hexafluoropropylene oxide homopolymer,  
 amide group-terminated  
 (surfactants, for inverse emulsion polymn. of acrylamide in  
 supercrit. carbon dioxide)

L42 ANSWER 16 OF 17 HCAPLUS COPYRIGHT 2001 ACS  
 ACCESSION NUMBER: 1993:562334 HCAPLUS  
 DOCUMENT NUMBER: 119:162334  
 TITLE: Reaction products of fluorine-containing  
 oligomers with aminoplasts and compositions  
 containing them for treatment of fibrous  
 substrates  
 INVENTOR(S): Dams, Rudolf J.; De Witte, Johan E.  
 PATENT ASSIGNEE(S): Minnesota Mining and Mfg. Co., USA  
 SOURCE: PCT Int. Appl., 57 pp.  
 CODEN: PIXXD2  
 DOCUMENT TYPE: Patent  
 LANGUAGE: English  
 FAMILY ACC. NUM. COUNT: 1  
 PATENT INFORMATION:

PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
WO 9217517	A1	19921015	WO 1992-US597	19920124
W: BR, CA, JP, KR				
RW: AT, BE, CH, DE, DK, ES, FR, GB, GR, IT, LU, MC, NL, SE				
US 5292796	A	19940308	US 1991-679652	19910402
CA 2105298	AA	19921003	CA 1992-2105298	19920124
EP 578743	A1	19940119	EP 1992-910094	19920124
EP 578743	B1	19980603		
R: AT, BE, CH, DE, DK, ES, FR, GB, GR, IT, LI, LU, MC, NL, SE				
JP 06505523	T2	19940623	JP 1992-509317	19920124
BR 9205829	A	19940823	BR 1992-5829	19920124
PRIORITY APPLN. INFO.:			US 1991-679652	19910402
			WO 1992-US597	19920124

AB Products having aminoplasts linked by O, S, NH, or CO<sub>2</sub>  
 bridges to oligomers having fluoroaliph. groups with fully  
 fluorinated terminal groups are manufd. for use as oil- and  
 waterproofing, stain-releasing, and softening agents for fibrous  
 substrates such as fabrics, paper, and leather. Thus, reaction of  
 hexamethoxymethylmelamine with 2-mercaptoethanol-  
 endcapped oligomeric poly(N-methylperfluorooctanesulfonamido  
 ethyl acrylate) gave a product (I). Cotton-polyester fabric was  
 treated with an aq. emulsion of I and Et cellulose and cured to give  
 fabric with good oil and water repellency after repeated laundering  
 and dry-cleaning.  
 IT 39420-94-5DP, reaction products with mercaptoethanol and  
 aminoplasts  
 (manuf. of, for finishes for fibrous substrates)  
 RN 39420-94-5 HCAPLUS  
 CN 2-Propenoic acid, 2-[[heptadecafluorooctyl)sulfonyl]methylamino]eth


yl ester, polymer with .alpha.-(1-oxo-2-propenyl)-.omega.-methoxypoly(oxy-1,2-ethanediyl) (9CI) (CA INDEX NAME)

CM 1

CRN 32171-39-4

CMF (C2 H4 O)<sub>n</sub> C4 H6 O2


CCI PMS



CM 2

CRN 25268-77-3

CMF C14 H10 F17 N O4 S



IC ICM C08G012-40

ICS D06M015-19

CC 40-9 (Textiles and Fibers)

Section cross-reference(s): 37, 43, 45

IT 60-24-2DP, 2-Mercaptoethanol, reaction products with aminoplasts and fluorine-contg. oligomers 68-11-1DP, Mercaptoacetic acid, reaction products with aminoplasts and fluorine-contg. oligomers 79-41-4DP, esters with di-Me siloxanes, reaction products with mercaptoethanol and methylperfluorooctanesulfonamidoethyl acrylate and aminoplasts 1854-26-8DP, Dimethyloldihydroxyethyleneurea, reaction products with mercaptoethanol and fluorooligomers 9003-08-1DP, Formaldehyde-melamine copolymer, reaction products with mercaptoethanol and fluorooligomers 27119-23-9DP, Poly(N-methylperfluorooctanesulfonamidoethyl acrylate), reaction products with mercaptoethanol and aminoplasts **39420-94-5DP**, reaction products with mercaptoethanol and aminoplasts 108388-39-2DP, reaction products with mercaptoethanol and aminoplasts 149545-17-5DP, reaction products with mercaptoethanol and aminoplasts 150179-37-6DP, reaction products with mercaptoethanol and aminoplasts (manuf. of, for finishes for fibrous substrates)

L42 ANSWER 17 OF 17 HCAPLUS COPYRIGHT 2001 ACS  
 ACCESSION NUMBER: 1969:413967 HCAPLUS  
 DOCUMENT NUMBER: 71:13967  
 TITLE: Perfluorinated rubbery polymers  
 PATENT ASSIGNEE(S): Minnesota Mining and Manufg. Co.  
 SOURCE: Fr., 8 pp.  
 CODEN: FRXXAK  
 DOCUMENT TYPE: Patent  
 LANGUAGE: French  
 FAMILY ACC. NUM. COUNT: 1  
 PATENT INFORMATION:

PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
FR 1524639		19680510	FR	19670526

AB The title polymers, which are resistant to solvents and stable at high temp., are prepd. from perfluorodi-carboxylic acids by pyrolysis of the corresponding Hg salts, and by uv irradiation or heating of the related nitriles in the presence of HCl. Thus, 10 g. of the Hg salt of perfluoro-4-oxaheptanedioic acid was heated 45 min. at 150-200.degree./16 mm. The temp. was then raised to 230.degree. in 10 min. and slowly to 300.degree. in 2 hrs., after which CO<sub>2</sub> evolution became quite slow. The pressure and temp. were then raised to 150 mm. and 350.degree. in the course of 2 hrs., and heating was continued at 345-65.degree. for 2 hrs., while allowing the pressure to rise to atm. The rubbery polymeric product was washed with HNO<sub>3</sub>, H<sub>2</sub>O, and Me<sub>2</sub>CO and agitated with a perfluorinated cyclic ether (FC 75) for 2 days. The resultant mixt. was filtered, and the insol. residue was dried in vacuo at 75.degree. to yield 0.5 g. of grayish elastomer, the ir spectrum of which indicated a structure [O(CF<sub>2</sub>)<sub>4</sub>]<sub>n</sub> **terminated** with **carboxyl groups**. Polymers were similarly prepd. from the Hg salts of perfluoroglutaric acid, a mixt. (I) contg. HO<sub>2</sub>C[CF(CF<sub>3</sub>)OCF<sub>2</sub>]<sub>3</sub>(CF<sub>2</sub>)<sub>4</sub>[CF<sub>2</sub>OCF(CF<sub>3</sub>)]<sub>3</sub>CO<sub>2</sub>H, HO<sub>2</sub>C[CF(CF<sub>3</sub>)OCF<sub>2</sub>]<sub>2</sub>(CF<sub>2</sub>)<sub>4</sub>[CF<sub>2</sub>OCF(CF<sub>3</sub>)]<sub>4</sub>CO<sub>2</sub>H, and HO<sub>2</sub>CCF(CF<sub>3</sub>)O(CF<sub>2</sub>)<sub>5</sub>[CF<sub>2</sub>OCF(CF<sub>3</sub>)]<sub>5</sub>CO<sub>2</sub>H, and the acid trimer from NC(CF<sub>2</sub>)<sub>3</sub>COCl, HO<sub>2</sub>C(CF<sub>2</sub>)<sub>5</sub>O(CF<sub>2</sub>CF<sub>2</sub>O)<sub>4</sub>CF<sub>2</sub>CO<sub>2</sub>H, and perfluorobutyric acid. In another example, the dinitrile of a mixt. (II) analogous to I with the formula C<sub>58</sub>F<sub>112</sub>O<sub>20</sub>H<sub>2</sub> was heated 8 hrs. at 200-50.degree. in a sealed tube in the presence of anhyd. HCl, after which HCl was removed in vacuo to give a rubbery product, which was insol. in perfluoroheptane (III) and contained triazine units. Irradiation of the dinitrile of II with unfiltered uv light also gave a rubbery solid which was insol. in III and contained polyazine units.

IC C08G  
 CC 38 (Elastomers, Including Natural Rubber)  
 IT Rubber, synthetic  
 (perfluoropolyether, manuf. of, from perfluorinated dicarboxylic acids)

=> d l43 1-4 ti

L43 ANSWER 1 OF 4 HCAPLUS COPYRIGHT 2001 ACS  
TI Laser-Induced Short Time Scale Thermal Chemistry of  
**Perfluoropolyether** Lubricant Films

L43 ANSWER 2 OF 4 HCAPLUS COPYRIGHT 2001 ACS  
TI Reactions of **perfluoropolyether** (PFPE) acids and their  
corresponding salts.

L43 ANSWER 3 OF 4 HCAPLUS COPYRIGHT 2001 ACS  
TI Structures and gas-separation properties of silicone-containing  
polyimides

L43 ANSWER 4 OF 4 HCAPLUS COPYRIGHT 2001 ACS  
TI Studies on silicone-grafted copolyimides. 3. Synthesis of soluble  
polyimide/poly(dimethylsiloxane) graft copolymer and application to  
separation membrane

=> d l43 1 ibib abs hitstr hitind

L43 ANSWER 1 OF 4 HCAPLUS COPYRIGHT 2001 ACS  
ACCESSION NUMBER: 1999:575453 HCAPLUS  
DOCUMENT NUMBER: 131:288574  
TITLE: Laser-Induced Short Time Scale Thermal Chemistry  
of **Perfluoropolyether** Lubricant Films  
AUTHOR(S): Heller, J.; Mate, C. M.; Poon, C. C.; Tam, A. C.  
CORPORATE SOURCE: FH Muenster, University of Applied Sciences  
Stegerwaldstrasse 39, Steinfurt, 48565, Germany  
SOURCE: Langmuir (1999), 15(23), 8282-8287  
CODEN: LANGD5; ISSN: 0743-7463  
PUBLISHER: American Chemical Society  
DOCUMENT TYPE: Journal  
LANGUAGE: English

AB We investigate the effect of heating a **perfluoropolyether**  
lubricant film in a localized area for relatively short time periods  
using laser irradiation vs. conventional oven heating. These experiments  
help provide understanding on how flash temps. generated at  
frictional contacts affect the thermal chem. of lubricant films. In  
these experiments, a CO<sub>2</sub> laser heats a 50 .mu.m wide area of a  
silicon wafer for time periods ranging from 0.1 to 60 s. The  
surface temp. within the heated area (up to 280 .degree.C in these  
experiments.) is monitored with a second laser by measuring the change in  
reflectivity near the center of the heated area. A major difference  
observed for laser heating compared to oven heating is that the  
effective evaporation rate is orders of magnitude higher for laser  
heating. If the lubricant film is heated for sufficiently long  
enough time at high temps., we are able to observe thermal bonding  
of the lubricant via its **alc. end groups** to the

silicon oxide surface, followed by thermal decompn. of the lubricant mols. After laser heating, we are able to observe the diffusion of lubricant back into the localized heated area using a combination of optical microscopy and imaging ellipsometry.

CC 51-8 (Fossil Fuels, Derivatives, and Related Products)

REFERENCE COUNT: 26

REFERENCE(S): (2) Cornaglia, L; J Vac Sci Technol A 1997, V15, P2755 HCAPLUS  
(3) Gao, C; IEEE Trans Magn 1995, V31, P2982 HCAPLUS  
(4) Gao, C; J Tribology 1999, V121, P97 HCAPLUS  
(5) George, S; Physical Methods of Chemistry 1993, V9A, P453 HCAPLUS  
(7) Hall, R; J Phys Chem 1987, V91, P1007 HCAPLUS

ALL CITATIONS AVAILABLE IN THE RE FORMAT

=> d l44 1-5 ti

L44 ANSWER 1 OF 5 HCAPLUS COPYRIGHT 2001 ACS

TI Electrophotographic photoreceptors using polycarbonates binder resin, process cartridge containing the photoreceptor, and electrophotographic apparatus

L44 ANSWER 2 OF 5 HCAPLUS COPYRIGHT 2001 ACS

TI Gas permeation properties of hyperbranched polyimide membranes

L44 ANSWER 3 OF 5 HCAPLUS COPYRIGHT 2001 ACS

TI Degradation of a branched perfluoropolyalkyl ether fluid with anhydrous aluminum chloride

L44 ANSWER 4 OF 5 HCAPLUS COPYRIGHT 2001 ACS

TI Electrophotographic photoreceptor using acrylic graft copolymer binder resin

L44 ANSWER 5 OF 5 HCAPLUS COPYRIGHT 2001 ACS

TI Manufacture of fluorine-containing **group-terminated** polymers